



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

**CERTIFICATE NO.: 2020011002320210**

## **NAME AND ADDRESS OF THE APPLICANT**

Vossloh-Schwabe Deutschland GmbH  
Hohe Steinert 8,D-58509 Ludenscheid, Germany

## **NAME AND ADDRESS OF THE MANUFACTURER**

Vossloh-Schwabe Deutschland GmbH  
Hohe Steinert 8,D-58509 Ludenscheid, Germany

## **NAME AND ADDRESS OF THE FACTORY**

Vossloh-Schwabe Serbia d.o.o.  
Karl Reum bb, 35210 SVILAJNAC SERBIA

## **PRODUCT NAME, MODEL AND SPECIFICATION**

A.C. Supplied Electronic Controlgear For LED Modules (Controlled Port Dimming (DALI) , Built-in, Auto-wound Controlgear, Constant Current Mode, ta: 50°C , tc: 70°C/65°C, Temperature Declared Thermally Protected: 130°C)

See Appendix. 220-240V ~ 50-60Hz, (198-276)VDC

## **THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS**

GB 17625.1-2012;GB/T 17743-2017;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO.CNCA-C10-01:2014).

**Valid from:** Sep.10,2020

**Valid until:** Sep.10,2025

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



President:

Lu Mei



**CHINA QUALITY CERTIFICATION CENTRE**



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

APPENDIX

Page 1 of 2

CERTIFICATE NO.: 2020011002320210

PAPER:

序号	型号	额定输入电压、频率	输出参数	ta	tc
1	ECXd 400.350	交流输入: 220-240V~ 50-60Hz (410-380)mA 直流输入: (198-276)VDC (410-380)mA	(100-400)mA , (100-225)Vdc, U out(max) 250Vdc, (10-85)W	50℃	70℃
2	ECXd 400.348	交流输入: 220-240V~ 50-60Hz (205-190)mA 直流输入: (198-276)VDC (205-190)mA	(100-400)mA , (30-120)Vdc, U out(max) 250Vdc, (3-40)W	50℃	65℃
3	ECXd 800.349	交流输入: 220-240V~ 50-60Hz	(400-800)mA , (30-70)Vdc, U out(max) 250Vdc, (12-40)W	50℃	70℃

**NOTE:** This appendix forms a part of the certificate for china compulsory product certification, and must be used together with the certification.



President:

Lu Mei

## CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

APPENDIX

Page 2 of 2

CERTIFICATE NO.: 2020011002320210

PAPER:

		(210-200) mA			
		直流输入: (198-276) VDC (210-200) mA			
4	ECXd 800.351	交流输入: 220-240V~ 50-60Hz (425-385) mA	(400-800) mA , (30-130) Vdc, U out (max) 250Vdc, (12-85) W	50°C	70°C
		直流输入: (198-276) VDC (425-385) mA			

**NOTE:** This appendix forms a part of the certificate for china compulsory product certification, and must be used together with the certification.



President:

Lu Mei

## CHINA QUALITY CERTIFICATION CENTRE



# 中国国家强制性产品认证证书

证书编号：2020011002320210

## 委托人名称、地址

Vossloh-Schwabe Deutschland GmbH  
Hohe Steinert 8, D-58509 Ludenscheid, 德国

## 生产者（制造商）名称、地址

Vossloh-Schwabe Deutschland GmbH  
Hohe Steinert 8, D-58509 Ludenscheid, 德国

## 生产企业名称、地址

Vossloh-Schwabe Serbia d.o.o.  
Karl Reum bb, 35210 SVILAJNAC 塞尔维亚

## 产品名称和系列、规格、型号

LED 模块用交直流电子控制装置（LED 控制装置，控制端口调光（DALI），内装式，自耦式，恒流模式， $t_a$ : 50°C， $t_c$ : 70°C/65°C，定温热保护：130°C）

见附件。220-240V~ 50-60Hz, (198-276)VDC

## 产品标准和技术要求

GB 17625.1-2012; GB/T 17743-2017; GB 19510.1-2009; GB 19510.14-2009

上述产品符合强制性产品认证实施规则 CNCA-C10-01:2014 的要求，特发此证。

发证日期：2020 年 09 月 10 日 有效期至：2025 年 09 月 10 日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书的相关信息可通过国家认监委网站 [www.cnca.gov.cn](http://www.cnca.gov.cn) 查询

经中国合格评定国家认可委员会认可 CNAS C001-P



主任：

陆楠

## 中国质量认证中心



# 中国国家强制性产品认证证书

附 录

第 1 页 共 2 页

证书编号：2020011002320210

纸 号：

序号	型号	额定输入电压、频率	输出参数	ta	tc
1	ECXd 400.350	交流输入： 220-240V~ 50-60Hz (410-380)mA 直流输入： (198-276)VDC (410-380)mA	(100-400)mA , (100-225)Vdc, U out(max) 250Vdc, (10-85)W	50℃	70℃
2	ECXd 400.348	交流输入： 220-240V~ 50-60Hz (205-190)mA 直流输入： (198-276)VDC (205-190)mA	(100-400)mA , (30-120)Vdc, U out(max) 250Vdc, (3-40)W	50℃	65℃
3	ECXd 800.349	交流输入： 220-240V~ 50-60Hz	(400-800)mA , (30-70)Vdc, U out(max) 250Vdc, (12-40)W	50℃	70℃

注：此附录与证书同时使用时有效。



主任：

## 中国质量认证中心



# 中国国家强制性产品认证证书

附 录

第 2 页 共 2 页

证书编号：2020011002320210

纸 号：

		(210-200) mA			
		直流输入： (198-276) VDC (210-200) mA			
4	ECXd 800.351	交流输入： 220-240V~ 50-60Hz (425-385) mA	(400-800) mA , (30-130) Vdc, U out(max) 250Vdc, (12-85) W	50°C	70°C
		直流输入： (198-276) VDC (425-385) mA			

注：此附录与证书同时使用时有效。



主 任： 陆 杨

## 中国质量认证中心